METHOD AND SYSTEM FOR PREVENTING UNAUTHORIZED SERVER INTERFERENCE IN AN INTERNET PROTOCOL NETWORK

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention relates to computer networks, and in particular to a method and system in an Internet Protocol (IP) network for detecting and neutralizing one or a plurality of unauthorized Dynamic Host Configuration Protocol (DHCP) servers.

2. Description of the Related Art:

Internet

The Internet is a global network of computers and computers networks (the "Net"). The Internet connects computers that use a variety of different operating systems or languages, including UNIX, DOS, Windows, Macintosh, and others. To facilitate and allow the communication among these various systems and languages, the Internet uses a language referred to as TCP/IP ("Transmission Control Protocol/Internet Protocol"). TCP/IP protocol supports three basic applications on the Internet:

(1) transmitting and receiving electronic mail,

(2) logging into remote computers (the "Telnet"), and

(3) transferring files and programs from one computer to another ("FTP" or "File Transfer Protocol").

IP Addresses

Routers are utilized to interconnect two networks by forwarding packets from one network to the other. The term "IP router" is also used because the routing function is part of the IP network layer of the TCP/IP protocol.

IP addresses are utilized by the IP protocol to uniquely identify a host on the Internet. Strictly speaking, an IP address identifies an interface that is capable of sending and receiving IP datagrams, and one system can have more than one of such interfaces. However, both hosts and routers must have at least one IP address, so this simplified definition is acceptable. IP datagrams (data packets exchanged between hosts) are transmitted by a physical network attached to the host, wherein each IP datagram contains a source IP address and a destination IP address.

IP addresses are represented by a 32-bit unsigned binary value which is usually expressed in a dotted decimal format. For example, 9.167.5.8 is a valid Internet address. This numeric form is utilized by the IP software. The mapping between the IP address and an easier-to-read symbolic name, for example myhost.ibm.com, is performed by a Domain Name System (DNS).

IP Subnets

Due to the explosive growth of the Internet, assigning IP addresses is not flexible enough to allow efficiently facilitate changes in local network configurations. Such changes might occur when a new type

of physical network is installed at a location. A
growing number of hosts within a local network may also
precipitate such configuration changes by requiring that
the local network split into two or more separate
networks. In addition, growing intranetwork distances
require to divide a network into smaller networks
separated by gateways.

The concept of subnets has been introduced to avoid
the need to request additional IP network addresses in
these cases. Subnets can be assigned locally, since the
original single network still appears as one IP network
with respect to the larger IP internetwork context. To
designate a subnet, the host number within an IP address
header is subdivided into a network number and a host
number. This second network is termed "subnetwork" or
"subnet". The original network now includes multiple
subnets, and an IP address associated therewith is
interpreted as:

<network number><subnet number><host number>.

The combination of the subnet number and the host
number is often termed "local address" or "local part".
Subnetting is implemented in such a way that it is
transparent with respect to remote networks. A host
within a network that includes subnets is aware of the
subnetting while hosts in outside networks are not (the
local hose still regards the local part of the IP address
as a host number).

The manner in which the local part of the IP address is divided into subnet number and host number is freely chosen by the local network administrator (i.e., any bits in the local part of the address can be utilized to designate a subnet). The division of the original local part of the IP address into a subnet and host name is performed utilizing a subnet mask which is a 32-bit number. Zero bits in a subnet mask indicate bit positions ascribed to the host number, and ones indicate bit positions ascribed to the subnet number. The bit positions in the subnet mask belonging to the network number are set to ones but are not utilized. Subnet masks, like IP addresses are usually written in dotted decimal form.

World Wide Web

With the increasing size and complexity of the Internet, tools that are often called navigators or navigation systems have been developed to help find information on the network. Navigation systems include standards such as Archie, Gopher and, most well-known, the World Wide Web ("WWW" or "the Web"). In addition to serving as an Internet-based navigation system, the Web is also an information distribution and management system for the Internet. The Web provides an end user with a seamlessly integrated format of information, including still images, text, audio and video. A user on the Web using a graphical user interface may transparently communicate with different host computers on the system, different system applications, and different information formats for files and documents including text, sound, and graphics.

Uniform Resource Locators

A resource of the Internet is unambiguously identified by a Uniform Resource Locator (URL), which is a pointer to a particular resource at a particular location. A URL specifies the protocol utilized to access a server (e.g. HTTP, FTP,..), the name of the server, and the location of a file on that server.

Hyper Text Transfer Protocol

Each Web page that appears on client monitors may appear as a complex document that integrates, for example, text, images, sounds and animation. Each such page may also contain hyperlinks to other Web documents so that a user at a client computer using a mouse may click on icons and may activate hyperlink jumps to a new page (which is a graphical representation of another document file) on the same or a different Web server.

A Web server is a software program on a Web host computer that answers requests from Web clients, typically over the Internet. All Web servers utilize a Hyper Text Transfer Protocol (HTTP) to communicate with Web clients. All types of data can be exchanged among Web servers and clients using HTTP, including Hyper Text Markup Language (HTML), graphics, sound and video. HTML describes the layout, contents and hyperlinks of the documents and pages. When browsing, a Web client converts user specified commands into HTTP GET requests, connects to the appropriate Web server to retrieve information, and waits for a response. The response from the server can be the requested document or an error message. After the document or an error message is

returned, the connection between the Web client and the
Web server is closed.

HTTP version 1.0 is a stateless protocol in which
there is no continuous connection between each client and
each server. A Web client using HTTP receives a response
as HTML data or other data. The new HTTP version 1.1
breaks this barrier of stateless protocol by keeping the
connection between the server and client alive under
certain conditions.

Domain Names

The host or computer names (like www.entreprise.com)
are translated into numeric Internet addresses (like
194.56.78.3), and vice versa, by using a method called
DNS ("Domain Name Service"). DNS is supported by
network-resident servers, also known as domain name
servers or DNS servers.

Dynamic IP

For dynamic IP there are generally three pieces of
information needed by a system to communicate on a TCP/IP
network. First, there is an IP address utilized to
uniquely identify a particular system on the network.
Next, a subnet mask is utilized to distinguish the
network and subnet parts of the address. Finally, an
address of at least one router is required if the system
communicates with devices outside its immediate subnet.

While at a minimum these three values must be
programmed into each device that participates in TCP/IP
communications, the number of necessary parameters will

often be much higher. Given the exponential growth rate of modern networks, the task of manually programming these values into every device attached to the network represents a major administrative workload.

The increasingly mobile nature of the end users also raises problems with regard to configuration of network devices. Allocating multiple sets of configuration parameters to a device requires an even greater workload for the network administrator. Multi-configuration allocation is also wasteful in terms of the sheer number of IP addresses allocated.

As explained next, several components of TCP/IP can automate device configuration, reduce the number of IP addresses allocated, and/or cope with the demands of mobile users.

Bootstrap Protocol (BOOTP)

The BOOTP protocol was originally developed as a mechanism to enable diskless hosts to be remotely booted over a network as workstations, routers, terminal concentrators, etc. Implementing BOOTP allows a minimal IP protocol stack with no configuration information required for obtaining sufficient information to begin the process of downloading the necessary boot code. While BOOTP does not define the manner in which the downloading is performed, TFTP "Trivial File Transfer Protocol (TFTP)" as described in *RFC 906 - Bootstrap Loading Using TFTP* is generally utilized. Although BOOTP is still widely utilized for remote booting of diskless hosts, itvis also commonly utilized as a mechanism that

delivers configuration information to a client that has
not been manually configured.

The latter BOOTP process involves the following
steps. First, a BOOTP client determines its own hardware
address, normally from a ROM (Read Only Memory) on the
hardware. Next the client sends its hardware address in
a UDP (User Datagram Protocol) datagram to the server.
The client should utilized its IP address and/or the
address of the server if it has these values. However,
BOOTP clients generally have no IP configuration data at
all. If the client does not know its own IP address, it
utilizes 0.0.0.0. If the client does not know the
server's IP address, it utilizes the limited broadcast
address (255.255.255.255) on the server's UDP port number
67.

After the server receives the datagram, it performs
a lookup to identify the hardware address of the client
in its configuration file. The hardware address contains
the client's IP address. The server then supplies the
required address information in the appropriate UDP
datagram fields, and returns the dataframe to the client
using client's UDP port 68. Upon receiving the reply,
the BOOTP client will record its own IP address and begin
the bootstrap process.

BOOTP is a recommended draft standard protocol.
BOOTP specifications can be found in *RFC 951 – Bootstrap
Protocol*. There are also updates to BOOTP, some relating
to inter operability with DHCP (Dynamic Host
Configuration Protocol) that are described in *RFC 1542 –*

Clarifications and Extensions for the Bootstrap Protocol,
which updates *RFC 951 and   RFC 2132 — DHCP Options and*
BOOTP Vendor Extensions.

Dynamic Host Configuration Protocol (DHCP)

Dynamic Host Configuration Protocol (DHCP) provides
a framework for passing configuration information to
hosts on a TCP/IP network. DHCP is based on the BOOTP
protocol, and adds the capability of automatically
allocating reusable network addresses and additional
configuration options. DHCP messages utilize UDP port
67, the BOOTP server's well-known port, and UDP port 68,
the BOOTP client's well-known port.

DHCP consists of two components including a protocol
that delivers host-specific configuration parameters from
a DHCP Server to a host, and a mechanism for the
allocation of temporary or permanent network addresses to
hosts.

IP requires the setting of many parameters within
the protocol implementation software. Because IP can be
utilized on many dissimilar types of network hardware,
values for those parameters cannot be presumed. A
distributed address allocation scheme based on a polling
/ defence mechanism, for discovering network addresses
currently in use, cannot guarantee unique network
addresses because hosts may not always be able to protect
their network addresses.

DHCP supports three mechanisms for IP address
allocation. First DHCP supports automatic allocation in

which DHCP assigns a permanent IP address to the host.
Second, DHCP supports dynamic allocation in which DHCP
assigns an IP address for a limited period of time.
Finally, DHCP supports manual allocation in which the
host's address is assigned by a network administrator.

DHCP is a draft standard protocol having an elective
status. The current DHCP specifications can be found in
RFC 2131 — Dynamic Host Configuration Protocol and *RFC
2132 — DHCP Options and BOOTP Vendor Extensions.*

Configuration Parameters Repository

DHCP provides persistent storage of network
parameters for network clients. A DHCP server stores a
key-value entry for each client. The key is a unique
identifier such as, for example, an IP subnet number and
a unique identifier within the subnet (normally a
hardware address). The key-value contains the
configuration parameters last allocated to this
particular client.

One effect of this persistent key-value storage is
that the server will always tend to allocate the same IP
address to a DHCP client, provided the pool of addresses
is not over-subscribed and the previous address has not
already been allocated to another client.

DHCP Considerations

DHCP allocation of IP addresses and configuration
parameters relieves the network administrator of a great
deal of manual configuration work. The ability to move a
device from network-to-network and to automatically

obtain valid configuration parameters for the current
network can be of great benefit to mobile users. Also,
because IP addresses are only allocated when clients are
actually active, it is possible, by the use of reasonably
short lease times and the fact that mobile clients do not
need to be allocated more than one address, to reduce the
total number of addresses in use in an organization.

However, the following should be considered when
implementing DHCP. First, DHCP is built on UDP, which
is, as yet, inherently insecure. In normal operation, an
unauthorized client could connect to a network and obtain
a valid IP address and configuration. To prevent this,
IP addresses can be preallocated to particular MAC
(Medium Access Control) addresses. This solution,
however introduces additional administrative workload and
negates the benefit of recycling addresses. Another
problem with DHCP is the possibility that unauthorized
DHCP servers may be implemented which send false and
potentially disruptive information to clients.

Regardless of whether static or dynamic address
allocation is utilized, it is generally not possible in a
DHCP environment to predetermine the IP address of a
client at any particular point in time. As such, the DNS
servers will not likely contain valid host-name-to-IP-
address mappings for the clients. The only alternative
is to manually assign IP addresses to clients and then
administer the client mappings in the DNS accordingly.

BOOTP and DHCP Interoperability

The format of DHCP messages is based on the format
of BOOTP messages, thus enabling BOOTP and DHCP clients
to interoperate in certain circumstances. Support for
BOOTP clients at a DHCP server must be configured by a
system administrator.

Dynamic Domain Name System

In order to take advantage of DHCP, while retaining
the capability to locate any specific host by means of a
meaningful label such as its host name, the following
extensions to the DNS are required. First, a method is
required for the host name to be addressed to a mapped
entry for a client in the domain name server to be
updated, once the client has obtained an address from a
DHCP server. A method is required for the reverse
address to host name mapping once the client obtains its
address.

In addition, updates to the DNS must take effect
immediately, without the need for intervention by an
administrator. Updates to the DNS must be authenticated
to prevent unauthorized hosts from accessing the network
and to stop imposters from using an existing host name
and remapping the address entry for the unsuspecting host
to that of its own. Finally, a method is required which
allows primary and secondary DNS servers to quickly
forward and receive changes as entries are being updated
dynamically by clients. In short, a secure Dynamic
Domain Name System (DDNS) is necessary.

In summary, in the DHCP and DDNS environment, DHCP
supplies a valid IP address to a device at the point in
time at which the device is attached to the network.
DDNS provides a method for locating that device within
the network in accordance with its host name, and for
determining the IP address allocated to the device.

More explanations about the domain presented in the
above sections can be found in the following publications
incorporated herewith by reference: TCP/IP Tutorial and
Technical Overview by Martin W. Murhammer, Orcun Atakan,
Stefan Bretz, Larry R. Pugh, Kazunari Suzuki, David H.
Wood published by IBM International Technical Support
Organization; "Internet in a nutshell" by Valerie
Quercia, published by O'Reilly, October 1997; Request For
Comments (RFCs) from the Internet Engineering Task Force
(IETF); and RFC 2131: Dynamic Host Configuration
Protocol.

When a DHCP client needs to acquire configuration
information such as an IP address (for instance when the
DHCP client is powered on), the DHCP client usually
broadcasts a request to retrieve the configuration
information from a DHCP server. The DHCP service is
provided by one or more DHCP servers, in order to
optimally adjust configuration parameters. Due to the
nature of the DHCP protocol which is based on UDP (User
Datagram Protocol) BOOTP broadcast, any DHCP server
attached to the IP network can answer requests from DHCP
clients and can therefore provide DHCP clients with
configuration parameters. The DHCP client selects and
utilizes the configuration parameters included within one

of the answers received from the DHCP servers (usually, the DHCP client selects and utilizes the configuration parameters received from the first DHCP server to respond).

Once a DHCP client has retrieved the requested configuration information (including its IP address) from a DHCP server, the DHCP client can then utilize the configuration information to access resources within the IP network. For example, a DHCP client utilizes its IP address to access a WEB server within the IP network.

Some access and security considerations are associated with the configuration information retrieved by DHCP clients. For example, the IP address retrieved and utilized by a DHCP client may be utilized by a WEB server to identify the DHCP client. The WEB server can then only respond to requests from the DHCP client having this specific IP address. The DHCP client configured with the specific IP address is therefore able to retrieve information from the WEB server (for example confidential information). A DHCP client configured with an IP address different from the specific IP address is not able to retrieve confidential information from the WEB server.

The nature of the configuration information provided by the DHCP servers may be determined by a network administrator. Erroneous configuration information may result in DHCP clients having problems accessing resources within the IP network. For example, a WEB server may only accept requests sent by DHCP clients that

have valid IP addresses (an IP address included within a
list of IP addresses controlled by the network
administrator). If the IP address retrieved from a DHCP
server by a DHCP client is incorrect (an IP address which
is not included within the list of valid IP addresses),
the WEB server will reject requests originated from the
DHCP client.

Inversely, an incorrect IP address provided to a
DHCP client may enable the DHCP client to access a WEB
server that the client should not have access to. A
security problem is thus presented because the DHCP
client may access confidential information it is not
supposed to access.

DHCP servers that provide DHCP clients with
erroneous configuration information are called
"unauthorized DHCP servers", or "invalid DHCP servers",
because they are not properly under the control of a
network administrator. Unauthorized DHCP servers may be
unintentionally attached to an IP network for example by
someone testing DHCP functions, or may be deliberately
attached to create access problems within the IP network.

From the foregoing, it can be appreciated that there
exists a need to detect any unauthorized DHCP server
attached to the IP Network. Furthermore it would be
useful to inhibit any unauthorized DHCP server attached
to the IP network from providing unauthorized access to
IP network resources.

SUMMARY OF THE INVENTION

A method and system for preventing unauthorized dynamic host configuration servers from responding to client configuration requests in an Internet Protocol (IP) network are disclosed herein. In accordance with the method of the present invention multiple network clients are simulated within a server checker client. At least one unauthorized dynamic host configuration server is then detected utilizing the server checker client within said IP network. Upon detection of an unauthorized dynamic host configuration server, configuration requests are delivered from the server checker client to the detected unauthorized dynamic configuration server such that the unauthorized dynamic host configuration server is unable to respond to configuration requests from actual network clients.

All objects, features, and advantages of the present invention will become apparent in the following detailed written description.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel and inventive features believed characteristics of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative detailed embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 illustrates a conventional IP host configuration system;

Figure 2 depicts a DHCP checker client in accordance with a preferred embodiment of the present invention;

Figure 3 is a flow diagram view illustrating the logic flow of an invalid server detector in accordance with a preferred embodiment of the present invention; and

Figure 4 is a flow diagram view depicting the logic flow of an invalid server denial handler in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

IP ADDRESS ALLOCATION

With reference now to the figures, and in particular with reference to **Figure 1** there is illustrated a conventional IP host configuration system in which DHCP client/server interactions are described in the context in which the DHCP client is not aware of its network address. More particularly, **Figure 1** shows the acquisition mechanism by which a DHCP client acquires an IP address and the IP minimal configuration parameters provided by a DHCP server within an IP network.

A DHCP client **101** broadcasts a request on its local physical subnet **103**. The request is forwarded by any router having a BOOTP forwarding mechanism. When the request is received by a DHCP server **102**, the DHCP server checks whether or not it is able to answer the DHCP client. If the DHCP server has an available IP address within its address database, a positive answer is returned to DHCP client **101**. DHCP client **101** selects the first DHCP server for which a positive answer is received and confirms to this server its agreement.

Specifically, the allocation of a new network address as described above includes the following steps. First, DHCP client **101** broadcasts a request (a DHCPDISCOVER message) on its local physical subnet **103**. The request may include desired options such as network address suggestion or lease duration.

Each DHCP server may respond with a message (a DHCPOFFER message) that includes an available network address and other configuration options. The DHCP server may record the address as offered to DHCP client **101** to prevent the same address being offered to other DHCP clients in the event of further messages being received before the first DHCP client has completed its configuration.

DHCP client **101** receives one or more messages from one or more of DHCP servers **102**. DHCP client **101** chooses one response based on the configuration parameters offered and broadcasts a message (a DHCPREQUEST message) that includes the DHCP server identifier option to indicate which message it has selected and the requested IP address option, taken from the DHCP client IP address in the selected offer.

DHCP servers **102** receive the messages broadcasted by DHCP client **101**. Those DHCP servers not selected utilize the message as notification that the DHCP client has declined that DHCP server's offer. The selected DHCP server commits the binding for the DHCP client to persistent storage and responds with a message containing the configuration parameters for the requesting DHCP client. The DHCP client receives the message with configuration parameters and performs a final check on the parameters. At this point the DHCP client is configured.

DHCP Checker Client

The present invention relates to a system and method for detecting and neutralizing unauthorized DHCP servers attached to an IP network. **Figure 2** depicts a system that is utilized for detecting and neutralizing unauthorized DHCP servers according to the present invention.

DHCP clients **201** on an IP network **202** retrieve their configuration information from DHCP servers **203** and **204** attached to the IP network. DHCP servers **203** are authorized DHCP servers that are controlled by a network administrator. Authorized DHCP servers **203** provide valid configuration information to the DHCP clients **201**.

One or more DHCP servers **204**, that are also attached to IP network **202**, are unauthorized DHCP servers (also referred to as an invalid DHCP server). They are not controlled by a network administrator and they provide invalid configuration information to the DHCP clients **201**. Such unauthorized DHCP servers may be unintentionally attached to IP network **202** by someone testing DHCP functions, or may be intentionally attached to sabotage IP network **202**.

As further illustrated in **Figure 2**, a DHCP checker client **205** is also attached to IP network **202** in accordance with the preferred embodiment of the present invention. DHCP checker client **205** is preferably a computer program that can run on any system (a workstation, for example) attached to IP network **202**.

DHCP checker client **205** carries out the method for detecting and neutralizing one (or multiple) unauthorized DHCP server **204**.

DHCP checker client **205** includes a DHCP server table **206**. DHCP server table **206** (a flat file in a preferred embodiment) may be created by the network administrator responsible for the IP network. DHCP server table **206** includes a list of authorized DHCP servers. Each authorized DHCP server **203** is preferably identified within DHCP server table **206** in accordance with its respective IP address.

When DHCP checker client **205** is started, an invalid server detector component **207** periodically sends requests **209** to retrieve configuration information **210** from DHCP servers **203** and **204**. Invalid server detector **207** detects one or more unauthorized DHCP servers **204** by comparing a "server identifier" option included in the DHCPOFFER message returned by the DHCP servers in configuration information **210** with authorized server identification data in DHCP server table **206**.

In response to one or more unauthorized DHCP servers **204** being detected by invalid server detector **207**, DHCP checker client **205** automatically activates an invalid server denial handler component **208**. Invalid server denial handler **208** simulates multiple DHCP clients by sending a large number of requests **211** to each unauthorized DHCP server **204** detected by invalid server detector **207**, for retrieving **212** configuration

information. The requests **211** include DHCPDISCOVER and DHCPREQUEST unicast messages, and utilizes 'giaddr', 'chaddr', and 'ciaddr' fields of the messages. The number of the requests depends on the configuration of the DHCP checker client.

By simulating multiple DHCP clients, invalid server denial handler **208** prevents unauthorized DHCP servers **204** from answering actual DHCP clients **201** that request configuration information. As a result, the number of DHCP clients **201** receiving erroneous configuration information by the unauthorized DHCP servers **204** is minimized. Additionally, access problems caused by the unauthorized DHCP servers are also minimized.

Unauthorized DHCP servers are, in effect, neutralized in response to invalid server denial handler **208** sending a large number of requests **211** to each unauthorized DHCP server **204**. This neutralization results from each unauthorized DHCP server **204** being overloaded with the requests and the corresponding configuration responses **212**. In response to configuration requests and the resulting responses **212**, many if not all of the IP addresses allocatable by unauthorized DHCP server **204** are reserved for DHCP checker client **205** and are therefore no longer available for other DHCP clients **201**.

After such neutralization, each is too busy to answer **214** requests **213** that are sent by DHCP clients **201**. Unauthorized DHCP server **204** is depleted of the

available IP addresses which can be provided to DHCP clients **201**. The number of DHCP clients **201** that may potentially retrieve **214** configuration information from unauthorized DHCP servers **204** is therefore minimized.

INVALID SERVER DETECTOR

Invalid server detector **207** is preferably a computer program that periodically requests and retrieves configuration information from DHCP servers **203** and **204**. Invalid server detector **207** identifies unauthorized DHCP servers **204** by comparing server identification data in DHCP server table **206** with the "server identifier" option included in the DHCPOFFER message returned **210** by the DHCP servers.

Invalid server detector **207** is activated when the DHCP checker client starts. With reference now to **Figure 3**, there is depicted a flow diagram illustrating the logic flow of invalid server detector **207** for detecting invalid DHCP servers in accordance with a preferred embodiment of the present invention.

As depicted at step **301**, the invalid server detection process begins with invalid server detector **207** requesting an IP address. During step **301**, DHCP checker client **205** appears as a typical DHCP client within respect to DHCP servers **203** and **204**. Invalid server detector **207** sends a DHCPDISCOVER message on the IP network, in order to request configuration parameters (including an IP address) from a DHCP server. The DHCPDISCOVER message is a broadcast message which is sent

to any system attached to the IP network.

Next, as shown at step **302**, invalid server detector **207** waits for DHCPOFFER messages. Each of DHCP servers **203** and **204** that satisfy the DHCPDISCOVER request sent by invalid server detector **207**, responds to the request with a DHCPOFFER message. The DHCPOFFER message includes the configuration information (including the IP address) proposed by the responding DHCP server. In addition the DHCPOFFER message includes the 'server identifier' option. The 'server identifier' option includes the address (the IP address) of the respondent DHCP server. The time over which invalid server detector **207** waits before receiving the DHCPOFFER message sent by each DHCP server is preferably a configuration parameter of DHCP checker client **205**.

Proceeding to step **303**, invalid server detector **207** releases the IP address proposed by each DHCP server. Authorized DHCP servers **203** may have sent a DHCPOFFER to propose configuration parameters. Invalid server detector **207** therefore releases the proposed configuration parameters so that they can be utilized by actual DHCP clients **201**. In order to release the IP address proposed by each DHCP server, invalid server detector **207** sends a DHCPREQUEST broadcast message that includes a 'server identifier' option. The 'server identifier' option is not set by invalid server detector **207** with the identifier of the DHCP server that has been selected, but instead includes the identifier (the IP address) of a DHCP server that does not exist (10.1.1.1,

for example).

When each DHCP server **203** and **204** receives the
DHCPREQUEST message, it compares the IP address included
within the 'server identifier' option and its own IP
address. Since the 'server identifier' and its IP
address are different, the DHCP server marks the proposed
configuration parameters as being available again for
other DHCP clients.

As illustrated at step **304**, invalid server detector
207 builds a list (called "List_R") of the DHCP servers
which have sent a DHCPOFFER. The list "List_R" includes
the IP address of each DHCP server to which the DHCPOFFER
message has been sent. In a preferred embodiment,
"List_R" is constructed using the 'server identifier'
option included in each DHCPOFFER message received in
202. The IP address of each DHCP server which has sent a
DHCPOFFER is extracted from the 'server identifier'
option.

Proceeding to step **305**, invalid server detector **207**
retrieves a list (called "List_A") of all authorized DHCP
servers. This list is retrieved from a DHCP server table
306 that is analogous to DHCP server table **206** in **Figure
2**. "List_A" includes the IP address of each authorized
DHCP server.

Invalid server detector **207** extracts from "List_R" a
list (called "List_D") of the DHCP servers which are not
in "List_A" as shown at step **307**. "List_D" therefore
includes the IP address of each unauthorized (also

referred to as invalid) DHCP server.

As depicted at step **308**, invalid server detector **207**
determines whether or not "List_D" is empty. If "List_D"
is determined to be empty, no unauthorized (invalid) DHCP
server has been detected, and as illustrated at step
309, invalid server detector **207** may store a message
indicating that no invalid DHCP server has been
detected. This message may be, for example, stored in a
file located within the DHCP checker client. The
operational cycle for invalid server detector **207** then
concludes as shown at step **310**. The DHCP checker client
then initiates another cycle in which invalid server
detector **207** begins the procedure for detecting
unauthorized DHCP servers starting at step **301**. The
inter-cycle period in which DHCP checker client **205** waits
before starting invalid server detector **207** is preferably
a configuration parameter of DHCP checker client **205**.

If, however, as depicted at step **311**, it is
determined at step **308** that "List_D" is not empty, one or
more unauthorized (invalid) DHCP servers have been
detected. In such a case, and as illustrated at step
311, invalid server detector **207** may store a message
indicating that one or multiple invalid DHCP servers have
been detected. This message may includes the IP address
of each the detected unauthorized DHCP servers, and is
stored in a file located within DHCP checker client **205**.
An network alert including the unauthorized server
message can also be sent to a network administrator. The
network administrator can then (for example) disconnect

each unauthorized DHCP server from the IP network.
Detection of an unauthorized server concludes as shown at
step **312**, with invalid server detector **207** calling
invalid server denial handler **208**.

INVALID SERVER DENIAL HANDLER

The invalid server denial handler component of the
DHCP checker client is preferably a computer program.
This component is responsible for: sending a large number
of requests to each unauthorized DHCP server **204**; and
retrieving **212** configuration information from each
unauthorized DHCP server **204** detected by the invalid
server detector component. The requests include
DHCPDISCOVER and DHCPREQUEST unicast messages, and
utilizes the 'giaddr', 'chaddr', and 'ciaddr' fields of
the messages. The number of the requests delivered from
invalid server denial handler is a configuration
parameter of the DHCP checker client.

The invalid server denial handler, such as invalid
server denial handler **208**, simulates multiple DHCP
clients to achieve the following goals. First, the
client simulation prevents, to the extent possible,
unauthorized DHCP servers **204** from responding to DHCP
clients **201** that request configuration information.
Client simulation further minimizes the number of DHCP
clients **201** to which erroneous configuration information
is provided by unauthorized DHCP servers **204** which in
turn minimizes network access problems caused by the
unauthorized DHCP servers.

These goals are achieved by sending a large number
of requests **211** to each unauthorized DHCP server **204**, in
order to overload each unauthorized DHCP server with the
requests and the corresponding answers **212** and to reserve
many if not all of the IP addresses allocatable by the
unauthorized servers for the DHCP checker client. These
reserved IP addresses are therefore no longer available
for actual DHCP clients **201**.

As a consequence of client simulation operations
performed by invalid server denial handler **208**, each the
unauthorized DHCP server **204** is too busy to answer **214**
requests sent **213** by actual DHCP clients **201**. The
unauthorized servers are thus depleted of available IP
addresses that can be provided to actual DHCP clients
201. In this manner, the number of DHCP clients that
retrieve **214** configuration information from the
unauthorized DHCP servers is minimized.

Invalid server denial handler **208** is called by
invalid server detector **207** when one or multiple
unauthorized (invalid) DHCP servers have been detected.
With reference now to **Figure 4**, there is illustrated a
flow diagram depicting the logic flow of invalid server
denial handler **208** in accordance with a preferred
embodiment of the present invention.

The operation of invalid server denial handler **208**
begins as depicted at step **401**, with invalid server
denial handler **208** retrieving the identity of one DHCP
server from "List_D". As previously explained with

reference to **Figure 3**, "List_D" includes the IP address of each unauthorized (invalid) DHCP server ("List_D" is built by the invalid server detector).

After retrieving the identity of the unauthorized server at step **401**, invalid server denial handler **208** determines if there is still at least one unauthorized DHCP server to process as shown at step **402**. If there is no DHCP server to process, all unauthorized DHCP servers detected by invalid server detector **207** have been processed by invalid server denial handler **208** and as illustrated at step **403**, client simulation operations of invalid server denial handler **208** are paused. DHCP checker client **205** periodically initiates unauthorized server detection cycles performed by invalid server detector **207**. The inter-cycle period between such cycles is preferably a configuration parameter of DHCP checker client **205**.

If, as determined at step **402**, there remains at least one unauthorized DHCP server to process, then as illustrated at step **404**, invalid server denial handler **208** sends multiple DHCPREQUEST messages to the next unprocessed DHCP server. Invalid server denial handler sends a large number of DHCPREQUEST messages to the specified DHCP server. The number of requests delivered is preferably a configuration parameter of DHCP checker client **205**. Each the DHCPREQUEST message sent at step **404** has the following characteristics. Each message is a unicast message having as its destination the specified unauthorized DHCP server. Since the message is a unicast

message, the traffic within the IP network is minimized,
and the impact of the traffic on the devices attached to
the IP network is minimized (as compared to a broadcast
message sent to all devices attached to the IP network).
For example, the DHCP clients attached to the IP network
do not have to waste time reading the unicast message (as
opposed to a broadcast message, where each DHCP client
has to read the broadcast message just to determine that
it does not have to answer it).

A 'ciaddr' field included in each the DHCPREQUEST is
set by invalid server denial handler **208** with an IP
address that is not included within the range of the
valid addresses utilized within the IP network. The
range of valid IP addresses may be, for example, a
configuration information of DHCP checker client **205,** as
provided by a network administrator. Since the
DHCPREQUEST request received by the DHCP server includes
an invalid (and therefore unknown) IP address in the
'ciaddr" field, a somewhat extended period of time will
be required by the DHCP server before it determines that
it cannot satisfy the request. During this time period,
the DHCP server is busy and therefore is usually not able
to respond to all the requests sent **213** by actual DHCP
clients **201.**

Proceeding to step **405**, invalid server denial
handler **208** sends multiple (preferably many) DHCPDISCOVER
messages to the unauthorized DHCP server. The number of
such discover messages sent by invalid server denial
handler **208** is preferably a configuration parameter of
DHCP checker client **205** (50 messages, for example). Each

DHCPDISCOVER message has the following characteristics. First, in a preferred embodiment of the present invention, each message is a unicast message having the unauthorized server as its destination. Since each message is an unicast message, the traffic impact of the messages within the IP network is minimized (as compared to a broadcast message that is sent to all devices attached to the IP network). For example, the DHCP clients attached to the IP network do not have to waste time reading the unicast message (as opposed to a broadcast message, where each DHCP client has to read the broadcast message just to determine that it does not have to answer it).

A 'chaddr' field included in each DHCPDISCOVER is set by invalid server denial handler **208** with a MAC address which is not included within a range of valid MAC addresses utilized within the IP network. The MAC address is therefore unknown within the IP network. The range of valid MAC addresses may be, for example, a configuration information of the DHCP checker client provided by a network administrator. This MAC address is selected such that it is not already utilized for another DHCPDISCOVER previously sent by the invalid server denial handler.

Since the DHCP server receives a DHCPDISCOVER request including a new unknown MAC address in the 'chaddr" field, the DHCP server reserves a new IP address for the MAC address. The IP address is reserved by the unauthorized server for DHCP checker client **205**, and is therefore no longer available for other DHCP clients **201**

which may request **213** configuration parameters from the
unauthorized DHCP server.

The DHCP server reserves one IP address for the DHCP
checker client, for each DHCPDISCOVER message. Since a
large number of DHCPDISCOVER messages are received by the
DHCP server, the DHCP server finally runs out of the
available IP addresses that can be provided to DHCP
clients **201**.

A 'giaddr' field included in each DHCPDISCOVER
message is set by invalid server denial handler **208** with
the IP address of DHCP checker client **205**. The DHCP
server therefore delivers its response to the request
with a DHCPOFFER message to the IP address of DHCP
checker client **205**.

Optionally, the DHCPDISCOVER request also includes
an "IP address lease time" option that is set to request
a very long lease time (one week, for example) or even an
infinite lease time. In such a case, the DHCP server
reserves the IP address of DHCP checker client **205** for a
very long associated with the MAC address included in the
'chaddr' field of the DHCPDISCOVER request. During the
period in which the IP address is reserved, the DHCP
server is not able to provide the IP address to the
actual DHCP clients **201**.

Next, as depicted at step **406**, invalid server denial
handler **208** waits for a message from the DHCP server.
The message may be, for example, a DHCPOFFER message in
response to a DHCPDISCOVER request. The period of time

over which invalid server denial handler **208** waits before
receiving the messages is preferably a configuration
parameter of DHCP checker client **205**.

Invalid server denial handler **208** then determines
whether or not there is a DHCPOFFER message available for
processing as shown at step **407**. The DHCPOFFER message
includes the configuration information proposed by the
DHCP server (including the proposed IP address). If
there is no DHCPOFFER message to process, the denial of
the specified DHCP server is complete. Other
unauthorized DHCP servers may have to be denied. The
invalid server denial handler loops to step **401** to
retrieve the next unauthorized DHCP server to process.

If, as determined at step **407** there is a DHCPOFFER
message to process in response to the DHCPDISCOVER
message sent to the DHCP server, and as illustrated at
step **408**, invalid server denial handler **208** sends a
DHCPREQUEST message to the DHCP server. This
DHCPREQUEST message is unicast to the specified DHCP
server in order to accept the IP address proposed in the
DHCPOFFER. The DHCPREQUEST is constructed in accordance
with the DHCP protocol, using the information retrieved
from the DHCPOFFER message. When the DHCP server
receives the DHCPREQUEST message, it definitively
reserves the proposed IP address, and this IP address
cannot be allocated to another DHCP client. Invalid
server denial handler then loops back to step **406** and
waits for another message.

It should be noted that the step of flooding each
unauthorized DHCP server with multiple IP address renewal
requests and the step of reserving as many IP addresses
as possible in each unauthorized DHCP server can be
implemented together in a single embodiment as described
above or independently in distinct embodiments.

ADVANTAGES

The present inventions provides the following
advantages.

Unauthorized DHCP servers are detected, and can for
example be physically removed from the IP network by a
network administrator.

The negative effects generated by unauthorized DHCP
servers within the IP network are limited. In particular,
the number of DHCP clients receiving configuration
information from the unauthorized DHCP servers is
minimized. When the configuration information is in
error, the number of DHCP clients in error is therefore
minimized.

The traffic required within the IP network for
detecting and neutralizing unauthorized DHCP servers is
minimized. In particular, no broadcast message is
utilized (only unicast messages are utilized) for the
denial of unauthorized DHCP servers. Because each device
within the IP network has to read broadcast messages, the
broadcast messages have usually a negative impact on the
performance of the devices. For example, a DHCP client
has to read each broadcast message, just to determine

that it does not have to answer it. Since no broadcast
message is utilized for neutralizing unauthorized DHCP
servers, the impact on the performance of each device
attached to the IP network is therefore minimized.

The quality of the DHCP Service is improved because
the impact within the IP network of the unauthorized DHCP
servers is limited. The number DHCP clients configured
with information in error is limited. Consequently, the
number of access problems within the IP network is also
limited.

The security within the IP network is improved.
Since the number of DHCP clients in error is minimized,
the risk of having DHCP clients configured with
information in error allowing access to confidential
information is limited.

No additional or specific hardware is required.

While the invention has been particularly shown and
described with reference to a preferred embodiment, it
will be understood that various changes in form and
detail may be made therein without departing from the
spirit, and scope of the invention.